order;

5

converting the first information to second information, the second information being represented according to a second number system of a second order, the second order being greater than the first order;

receiving first information represented according to a first number system of a first

representing the second information using a first number of unique signal characteristics, the first number corresponding to the second order; and transmitting the second information via the transmission medium.

- 2. The method of claim 1 wherein the first number system is a binary number system.
- 3. The method of claim 2 wherein the second number system is a ternary number system.
- 20 4. The method of claim 2 wherein the second number system is a quaternary number system.
 - 5. The method of claim 2 wherein the second number system is a hexadecimal number system.

l= 15

15

20

- 6. The method of claim 2 wherein the second number system comprises an nth order number system where n is greater than or equal to three.
- 7. The method of claim 1 wherein each of the unique signal characteristics comprises a unique frequency.
 - 8. The method of claim 1 wherein the transmission medium comprises a wide area network.
 - 9. The method of claim 1 wherein at least a portion of the transmission medium comprises telephone transmission lines.
 - 10. A method for receiving information transmitted via a transmission medium, comprising:

receiving first information via the transmission medium, the first information being represented and transmitted using a first number of signal characteristics;

converting representation of the first information to a first number system of a first order, the first order corresponding to the first number; and

converting the first information to second information, the second information being represented according to a second number system of a second order, the second order being less than the first order.

11. The method of claim 10 wherein the second number system is a binary number system.

- 12. The method of claim 11 wherein the first number system is a ternary number system.
- 13. The method of claim 11 wherein the first number system is a quaternary number system.

A THE PART HAS REALLY BY PROPERTY DAY TO SEE THE PARTY OF THE PARTY OF

The line was one than the line will be the line with the line was one than the line will be the line with the line was one than the line was one than the line was one than the line was one to be the line was one than the line was one than the line was one to be the line was

13 14 15

20

25

- 14. The method of claim 11 wherein the first number system is a hexadecimal number system.
- 15. The method of claim 11 wherein the first number system comprises an nth order number system where n is greater than or equal to three.
- 16. The method of claim 10 wherein each of the unique signal characteristics comprises a unique frequency.
- 17. The method of claim 10 wherein the transmission medium comprises a wide area network.
- 18. The method of claim 10 wherein at least a portion of the transmission medium comprises telephone transmission lines.
- 19. A system for transmitting information via a transmission medium, comprising a transmitting station configured to receive first information represented according to a first number system of a first order, convert the first information to second information, the second information being represented according to a second number system of a second

order, the second order being greater than the first order, represent the second information using a first number of unique signal characteristics, the first number corresponding to the second order, and transmit the second information via the transmission medium.

5

The first part bear of the Call part of the case where the case wh

in the part and the part of th

A system for receiving information transmitted via a transmission medium, 20. comprising a receiving station configured to receive first information via the transmission medium, the first information being represented and transmitted using a first number of signal characteristics, convert representation of the first information to a first number system of a first order, the first order corresponding to the first number, and convert the first information to second information, the second information being represented according to a second number system of a second order, the second order being less than the first order.